

Digital Epaper line, with high-resolution graphical display provides exceptional contrast and viewing angles.



Low energy consumption

All Altierre models come with multi-year battery life warranty



A Complete 2 way communication

Management and communication tool

Altierre labels come with 4 programmable memory screens. This enables access to all relevant data for store associates. Essential information such as inventory, delivery date, planogram data, rotation date, etc, can be displayed in secondary screens to optimize operations.



Altierre bi-directional communication to the tags not only acknowledges receipt but also reports back on current display information and battery level. At any time the store knows the exact status of every tag.



A Full range of tags


With 6 unique sizes, Altierre offers the widest range of Graphical e-paper tags in the marketplace to cover all your needs and installations requirements.



- High contrast & resolution
- Very low energy consumption
- Two-way radio communication
- 5 years battery life
- Replaceable batteries
- High visibility from all angles
- Optional third color (red or yellow)
- 6 available sizes
- Additional screens for operational data



Attachment solutions suited to all types of store fixtures



Altierre has developed with its partners various attachment solutions which include rails with integrated angle adjustments and individual attachments. Point Of Purchase material and tag customizations are also available for more effective marketing & merchandising.



Technical specifications

	e-tag 150 E	e-tag 210 E	e-tag 290 E	e-tag 420 E	e-tag 580 E	e-tag 740 E	
Models							
Dimensions	ESL : W x H x D (mm)	46.6 x 39.1 x 17.3	66.8 x 36.8 x 14.0	86.9 x 43.9 x 13.8	100.8 x 85.8 x 13.5	136.3 x 115.5 x 13.5	185.1 x 134.4 x 20.4
Display specifications	Display: W x H (mm)	27.6 x 27.6	48.6 x 23.8	66.9 x 29.1	84.8 x 63.6	118.8 x 88.3	161.6 x 97.0
	Display: Diagonal (mm)	39	54.1	79.2	106	148	188.5
	Screen area (mm ²)	762	1,155	1,944	5,393	10,490	15,670
	Screen: W x H (Pix)	200 x 200	212 x 104	296 x 128	400 x 300	600 x 448	800 x 480
	Technology	E-Paper	E-Paper	E-Paper	E-Paper	E-Paper	E-Paper
	Number of programmable screens	4	4	4	4	4	4
	Animation / scrolling display	No	No	No	No	No	No
	Operating temperature	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C
Technical specifications	Operating humidity	25-60 % Non- condensing	25-60 % Non- condensing	25-60 % Non- condensing	25-60 % Non- condensing	25-60 % Non- condensing	25-60 % Non- condensing
	Power	Lithium coin cell batteries	Lithium coin cell batteries	Lithium coin cell batteries	Lithium coin cell batteries	Lithium coin cell batteries	Lithium coin cell batteries
	Battery life	5 years	5 years	5 years	5 years	5 years	5 years
Radio Frequency	ISM Band : 2400-2483,5 MHz	ISM Band : 2400-2483,5 MHz	ISM Band : 2400-2483,5 MHz	ISM Band : 2400-2483,5 MHz	ISM Band : 2400-2483,5 MHz	ISM Band : 2400-2483,5 MHz	



Altierre Corporation
1980 Concourse Drive, San Jose,
CA 95131, USA
Tel.: +1 408-435-7343

Visit our new website :
altierre.com

Altierre Europe Middle East and Africa
88 ter, avenue du Général Leclerc
92100 Boulogne Billancourt- France
Tél.: +33 1 74 31 14 40
Fax : +33 1 74 31 14 10